

## Internal unit 2-wire version

### General features:

- 7" TFT LCD monitor
- Two-way audio with built-in speaker and microphone
- Communications: TCP/IP, via 2-wire/IP converter, WiFi, SIP
- Input for microSD up to 32GB
- Image recording and capture
- Internal calls
- Surface mount
- APP notification

### Technical specifications:

<b>LCD</b>	Capacitive TFT 7"1024x600
<b>Operation</b>	Touchscreen
<b>Input</b>	8 configurable alarm inputs
<b>Output</b>	2 relay outputs
<b>Audio</b>	2-way audio with noise reduction
<b>Remote access</b>	Smartphone App or PC software
<b>Memory</b>	Input for microSD up to 32GB
<b>Network interface</b>	2wires / RS485 / RSTP / WiFi 802.11b/g/n (only for connection to the App via P2P)
<b>Power supply</b>	Through dedicated Hub for 2wire video intercom 6W max
<b>Operating temp.</b>	-10° C ~ +55° C
<b>Size / weight</b>	200 (L) x 140 (H) x 15,1 (W) mm / 355g

## Internal unit IP version

### General features:

- 7" IPS LCD monitor
- Tempered glass panel and metal frame
- Two-way audio with built-in speaker and microphone
- Communications: TCP/IP, RTSP, WiFi, SIP
- Input for microSD up to 32GB
- Image recording and capture
- Internal calls
- Surface mount
- APP notification

### Technical specifications:

<b>LCD</b>	Capacitive IPS 7"1024x600
<b>Operation</b>	Touchscreen and a button for unlocking the lock
<b>Input</b>	8 configurable alarm inputs
<b>Output</b>	2 relay outputs
<b>Audio</b>	2-way audio with noise reduction
<b>Remote access</b>	Smartphone App or PC software
<b>Memory</b>	Input for microSD up to 32GB
<b>Network interface</b>	Ethernet 10/100 BaseT / RS485 / RSTP / WiFi 802.11b/g/n (only for connection to the App via P2P)
<b>Power supply</b>	12Vdc 1A / standard PoE (IEEE802.3af)
<b>Operating temp.</b>	-10° C ~ +55° C
<b>Size / weight</b>	180 (L) x 140 (H) x 22,4 (W) mm / 355g



Technical specifications

Video intercom system (internal unit)

DESIGN EXCLUSIVELY OWNED BY MARINOX SRL, WHICH RESERVES ALL LEGAL RIGHTS