

Standard IP internal unit

(also available in 2-wire version)

General features:

- 7" TFT LCD monitor
- Two-way audio with build-in speaker and microphone
- Communications: TCP/IP, RSTP, WiFi, SIP
- Input for microSD up to 32GB
- Image recording and capture
- Internal calls
- Surface mount
- APP notification

Tecnical specifications:

LCD	Capacitive TFT 7"1024x600
Operation	Touchscreen
Input	8 configurable alarm inputs
Output	2 relay outputs
Audio	2-way audio with noise reduction
Remote access	Smartphone App or PC Software
Memory	Input for microSD up to 32GB
Network interface	RJ-45 0/100 self-adaptive / RS-485
Power supply	12Vdc 1A / standard PoE (IEEE802.3af)
Operating temp.	-10° C ~ +55° C
Size / weight	200 (L) x 140 (H) x 15,1 (P) mm / 355g

Reddot IP internal unit

General features:

- 7" IPS LCD monitor
- Tempered glass panel and metal frame
- Two-way audio with build-in speaker and microphone
- Communications: TCP/IP, RSTP, WiFi, SIP
- Input for microSD up to 32GB
- Image recording and capture
- Internal calls
- Surface mount
- APP notification

Tecnical specifications:

LCD	Capacitive IPS 7"1024x600
Operation	Touchscreen and a button for unlocking the lock
Input	8 configurable alarm inputs
Output	2 relay outputs
Audio	2-way audio with noise reduction
Remote access	Smartphone App or PC Software
Memory	Input for microSD up to 32GB
Network interface	RJ-45 0/100 self-adaptive / RS-485
Power supply	12Vdc 1A / standard PoE (IEEE802.3af)
Operating temp.	-10° C ~ +55° C
Size / weight	180 (L) x 140 (H) x 22,4 (P) mm / 355g

Android IP internal unit

General features:

- 7" TFT LCD monitor
- Android 10.1 operating system
- Two-way audio with build-in speaker and microphone
- Communications: TCP/IP, RSTP, WiFi, SIP
- Input for microSD up to 128GB
- Image recording and capture
- Internal calls
- Surface mount
- APP notification
- Android APP installation available

Tecnical specifications:

LCD	Capacitive TFT 7"1024x600
Operation	Capacitive touchscreen
Input	8 configurable alarm inputs
Output	1 relay outputs / 1 alarm output
Audio	2-way audio with noise reduction
Remote access	Smartphone App or PC Software
Memory	Input for microSD up to 128GB
Network interface	RJ-45 0/100 self-adaptive / RS-485
Power supply	12Vdc 1A / standard PoE (IEEE802.3af)
Operating temp.	-10° C ~ +50° C
Size / weight	187 (L) x 137 (H) x 25,7 (P) mm / 419g



Technical specifications

Video intercom system (internal unit)

DESIGN EXCLUSIVELY OWNED BY MARINOX SRL, WHICH RESERVES ALL LEGAL RIGHTS